

EUREKA 13-4 HEAT AF-17



PRODUCT CODE: E13-4HAF-17



PRODUCT INFORMATION:

- High cut resistance - EN388 Level E / ANSI Cut Level A5.
- Puncture resistance to 100N.
- Optimized for medium Arc Flash risks.
- Contact heat resistant over 100°C.
- High flame resistance.
- Arc flash protection ASTM F2675:
 - ATPV = 17,1 Cal/cm² (Back of hand)
 - ATPV = 57,9 Cal/cm² (Palm)
 - EN 61482-1-2 Modified by Aitex (Box Test) = APC 2
 - NFPA 70E = Level 2
- Contains 1% Anti-Static fibre
- Perfect in tough working conditions with high spark, heat and flame risks.
- High tear resistance up to 75N.
- Coated palm provides good grip in dry and wet/oily environments.
- Patent Pending Eureka Arc Flash Dot Technology.
- Reinforced thumb crotch.
- Breathable.

AVAILABLE IN:

PRODUCT CODE	SIZES	MOQ	CTN QTY
E13-4HAF-17-(SIZE)	7/XS - 12/2XL	12 PAIRS	60 PAIRS

CARE INSTRUCTIONS:



PERFORMANCE DATA:

ANSI Cut Level (2016):	A5
EN 388:	3X42E
EN Abrasion Level:	3
EN Cut Level - Coup Test:	X
EN Tear Level:	4
EN Puncture Level:	2
EN Cut Level - TDM100 Test:	E

STANDARDS:

